INDEPENDENCE GROUP NL

Diggers and Dealers Nova Project Site Visit 3 August 2016





Cautionary statements & disclaimer

- This presentation has been prepared by Independence Group NL ("IGO") (ABN 46 092 786 304). It should not be considered as an offer or invitation to subscribe for or purchase any securities in IGO or as an inducement to make an offer or invitation with respect to those securities in any jurisdiction.
- This presentation contains general summary information about IGO. The information, opinions or conclusions expressed in the course of this presentation should be read in conjunction with IGO's other periodic and continuous disclosure announcements lodged with the ASX, which are available on the IGO website. No representation or warranty, express or implied, is made in relation to the fairness, accuracy or completeness of the information, opinions and conclusions expressed in this presentation.
- This presentation includes forward looking information regarding future events, conditions, circumstances and the future financial performance of IGO. Often, but not always, forward looking statements can be identified by the use of forward looking words such as "may", "will", "expect", "intend", "plan", "estimate", "anticipate", "continue" and "guidance", or other similar words and may include statements regarding plans, strategies and objectives of management, anticipated production or construction commencement dates and expected costs or production outputs. Such forecasts, projections and information are not a guarantee of future performance and involve unknown risks and uncertainties, many of which are beyond IGO's control, which may cause actual results and developments to differ materially from those expressed or implied. Further details of these risks are set out below. All references to future production guidance made in relation to IGO are subject to the completion of all necessary feasibility studies, permit applications and approvals, construction, financing arrangements and access to the necessary infrastructure. Where such a reference is made, it should be read subject to this paragraph and in conjunction with further information about the Mineral Resources and Ore Reserves, as well as any Competent Persons' Statements included in periodic and continuous disclosure announcements lodged with the ASX. Forward looking statements in this presentation only apply at the date of issue. Subject to any continuing obligations under applicable law or any relevant stock exchange listing rules, in providing this information IGO does not undertake any obligation to publically update or revise any of the forward looking statements or to advise of any change in events, conditions or circumstances on which any such statement is based.
- There are a number of risks specific to IGO and of a general nature which may affect the future operating and financial performance of IGO and the value of an
 investment in IGO including and not limited to economic conditions, stock market fluctuations, commodity demand and price movements, access to infrastructure, timing
 of environmental approvals, regulatory risks, operational risks, reliance on key personnel, reserve and resource estimations, native title and title risks, foreign currency
 fluctuations and mining development, construction and commissioning risk. The production guidance in this presentation is subject to risks specific to IGO and of a
 general nature which may affect the future operating and financial performance of IGO.
- Any references to IGO Mineral Resource and Ore Reserve estimates, except the Nova Ore Reserve should be read in conjunction with IGO's 2015 Mineral Resource and Ore Reserve announcement dated 28 October 2015 and lodged with the ASX, which are available on the IGO website. The Nova Ore Reserve was updated during the optimisation study dated 14 December 2015 and lodged with the ASX, which is available in the IGO website. IGO confirms that it is not aware of any new information or data that materially affects the information included in the original announcements and all material assumptions and technical parameters underpinning the estimates of Mineral Resources and Ore Reserves in those announcements continue to apply and have not materially changed.
- All currency amounts in Australian Dollars unless otherwise noted.
- Cash Costs are reported inclusive of Royalties and after by-product credits on per unit of payable metal basis, unless otherwise stated.

World class Ni-Cu-Co project in construction

Overview

- IGO 100% owned magmatic Ni–Cu-Co project
- 1.5Mtpa underground mine
- Construction 93% complete
- On time and on budget for first concentrate production in December 2016
- Large scale, low cost production


Key developments and potential

- IGO has delivered 50% improvement in NPV since acquisition ⁽¹⁾
- Acceleration of Bollinger development
- A number of other value enhancement opportunities include increasing mining and processing rates

LOM Mining Inventory

		Tonnes (Mt)	Grade Ni (%)	Grade Cu (%)	Grade Co (%)	Contained Ni (kt)	Contained Cu (kt)	Contained Co (kt)		
Mineral Resource	Indicated	13.2	2.1	1.0	0.08	275	112	9		
Additional Resources	Inferred	1.4	1.0	0.6	0.05	14	6	1		
Total N Inven		14.6	2.0	0.8	0.1	289	119	10		

1) For further information see ASX release 21 July 2016 Accelerated Bollinger Decline at Nova Project Note: For further information see ASX release 14 December 2015 Nova Project Optimisation Study



Construction is on time and on budget

- Preliminary operating guidance for Nova provided through to FY19
- Additional opportunities exist to improve mining production and processing rates
- These further enhancements will be pursued following commissioning and ramp up

	Units	FY17 ⁽¹⁾	FY18	FY19
Nickel Production	tonnes	9,000 to 10,000	27,000 to 30,000	27,000 to 30,000
Copper Production	tonnes	3,900 to 4,400	12,000 to 13,000	12,000 to 13,000
Cobalt Production	tonnes	280 to 320	900 to 1,000	900 to 1,000
Cash costs (real) ⁽²⁾	A\$/lb Ni	4.00 to 4.50	1.50 to 2.00	1.50 to 2.00
Remaining Initial Capital Cost ⁽³⁾	A\$M	140 to 150	0	0
Sustaining Capex	A\$M	3 to 5	25 to 30 ⁽⁴⁾	5 to 7 ⁽⁴⁾
Development Capex	A\$M	22 to 25		
Exploration expenditure	A\$M	3.5 to 4.5		

1) FY17 excludes production achieved during commissioning

2) Cash costs includes C1 cash costs + royalty per pound of payable nickel (after by-product credits)


3) Remaining Initial Capital Costs includes the key capital activities (outstanding from the \$443M Project Capital Costs) outlined in the company's 28 June 2016 release titled "First Ore Mine in Development at Nova" including but not limited to capital on, the power station, plant piping/ electronical, past plant and decline development. The amount also includes capital required for the Bollinger Decline as outlined in this ASX release

4) Sustaining capex includes Development capex

Note: for further information on Nova production guidance see ASX release 21 July 2016 Accelerated Bollinger Decline at Nova Project and also refer to Important notices and disclaimer


Improved mining schedule delivers significant benefits

- IGO has delivered significant enhancement in project value compared to the DFS
- Optimisation Study completed in December 2015 moved Nova down the cost curve
- Optimisation Study delivered 36% improvement in NPV⁽¹⁾
- FY17 LOM realised an additional 14% improvement in NPV by accelerating Bollinger development⁽²⁾
- Optimisation study generated increases of 41%, 108% and 83% of free cash flow in CY17, CY18 and CY19 when compared to the DFS ⁽¹⁾
- FY17 LOM increased FY18 cash flow by an additional $A\$134M^{(2)}$




1) For further information see ASX release 14 December 2015, Nova Project Optimisation Study

2) For further information see ASX release 21 July 2016, Accelerated Bollinger Decline at Nova Project




FY17 LOM free cash flow relative to Optimisation Study⁽²⁾




Key milestone





Location map

- Nova is located 130km East of Norseman on the Eyre Highway.
- A sealed, purpose built road links site to the Eyre Highway
- Concentrates to be hauled to both Kambalda and Esperance



Underground access


Nova Decline

- Total underground development PTD 6.3km
- Developed 5.1km in FY16

Bollinger Decline

- Commenced in July 2016
- Independent access will deliver value to the project by:
 - Accelerated ramp-up to nameplate in FY17 and FY18
 - Enables consistent production
 - Deliver high NSR valued ore from Bollinger earlier
 - Two independent haulage routes which will increase haulage efficiencies
 - Increase flexibility of stoping, with two discrete mining areas

Underground layout



Ore Reserves (ASX Release 14 December 2015)

- Nova has total of 10.9Mt @ 2.0%Ni, 0.8%Cu & 0.06%Co
- Bollinger has total of 2.7Mt @ 2.2%Ni, 0.9%Cu & 0.09%Co

Underground infrastructure

Primary ventilation network

- FAR(Fresh Air Rise) # 1, 5.5m diameter rise completed.
- RAR(Return Air Rise) #1, pilot hole drilled to depth, mining around to place 5.5m head for back reaming.
- FAR #2, winzing (shaft sinking) from the surface down solid rock prior to raise boring.
- Primary fans on order.

Dewatering

- 2030 pumping chamber developed, rising main drilled, now installing rising main pipework.
- Staged approach with additional pumping stations required in Nova and Bollinger.

High Voltage Electrical network

- Two HV droppers to setup ring main.
- Two underground high voltage substations have been installed.

Non-processing infrastructure







- Access to site is either from 33km sealed, all weather, road from Eyre Highway or 2km sealed airstrip.
- Centralised workshop consisting of 4 bay heavy vehicle, boilermaker, electrical and light vehicle work areas.
- Raise bore insitu ready to raise a 5.5m rise to form RAR 1.
- Paste plant is rated at 168 wet tonnes of paste per hour.

Underground grade control

Diamond Drilling


- Drilling started in late May 2016
- 3 x Swick diamond drills on site
- Prioritising Infill drilling to increase knowledge
- Drilled a total 16.6km to date

Ore Development

 Developing ore drives on the 2030mRL, 2055mRL and 2080mRL

Grade control

 Grade control drilling to-date indicates positive ore volumes, when compared to 2015mRL and 2045mRL block model strings. Grades awaiting assaying to reconcile metal.



from DFS

2030 level






9 July 2016: Brecciated sulphides on Sediment – Gabbro Contact 29 June 2016: Massive and Stringer sulphide in Gabbro


13

2055 level





2080 level



2 July 2016: Brecciated Sulphide with clasts of Gabbro



28 June 2016: Brecciated Sulphide in Sed-Sed contact

Processing timeline: currently 93% complete

	2015															20	16									201	7		
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Jan	Feb	Mar	Apr	Ma
Underground																													
Boxcut excavation		_																											
Decline development																		_											
Paste plant														-			-												
Process Plant																													
Design										1	-																		
Procurement					0									_															
Construction							i.		_	-		-						-											
Commissioning								1															_						
Ramp up																													
First concentrate																													
Infrastructure																								T					
Accommodation		_	_	_	_	_	_	4																					
Access road	-	_	_	_	_	_	_	_	_	_	_	_																	
Airstrip					_	_	_	_																					
Water treatment			-	_	_	_	_																						
Power Station									-	_	_	_	_	_	-	_	_	-	_	-	_	_							
Workshops										_	_	_	_	_	_	_													

First Concentrate Production

Processing infrastructure








Crushing & Grinding

- Conventional flotation concentrator processing plant, with nameplate capacity of 1.5Mtpa.
- Primary crusher is a Metso C120 single jaw crusher, rated at 250t/hr. Typical jaw setting will be around 120-130mm.
- Feed from primary crusher flows into grinding circuit, which consists of a 1.6MW SAG & 2.2MW ball mills. The SAG mill is in open circuit and ball mill in closed circuit producing a 106 micro passing P80 product.
- Cyclone overflow feed reports to the flotation circuit.

Processing infrastructure








Flotation & Thickening Areas

- From the grinding circuit material flows into the copper conditioner, then copper flotation circuit. The high copper concentrate is thickened and pumped into the copper filter. The copper tailings stream flows into the nickel flotation circuit from where the nickel concentrate is thickened and pumped to the nickel filter. Both circuits have a regrind capacity.
- The concentrate storage shed has been designed specifically to ensure separation of the copper and nickel concentrates. The shed also accommodates the weight bridge which also serves to separate the copper and nickel products.
- The copper and nickel filter presses are located in this shed and during the filtration cycles the concentrate is washed with fresh water prior to being squeezed under pressure to dewater, leaving the concentrate product with a targeted 7-9% moisture level.

Sustainability: a core IGO value



FOLLOW US AS WE GO FROM STRENGTH TO STRENGTH igo.com.au

211

IQO